

Refrigerator Water Filter Models: W-3

This system has been certified according to NSF/ANSI Standard 42 and 372 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42 and 372.

Contaminant	% of reduction	Influent Concentration	Max Allowable
NSF/ANSI 42 - AESTHETIC EFFECTS			
CHLORINE*	>97%	2.0 mg/L	1.0 mg/L

* Certified by NSF International.

* Certified by IAPMO R&T.

FILTER SPECIFICATIONS

Flow Rate:	0.5 gpm / 1.89 lpm
Operating Temperature:	33 - 100°F (0.6°C - 38°C)
Operating Pressure:	30 psi (207 kPa) - 100 psi (689 kPa)
Capacity:	300 gallons (1,136 L) or six months



Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



Certified by IAPMO against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.

Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. The system conforms to NSF/ANSI 42 and 372 for the specific performance claims as verified and substantiated by test data. See above for individual contaminants and reduction performance. Note: Testing was performed under standard laboratory conditions, actual performance may vary.

System to be used with municipal or well water sources treated and tested on regular basis to ensure bacteriological safe quality. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. Manufactured by Aquamor, LLC, Temecula, CA.

Limited Warranty: This filter hereunder shall be free from material defects in material and workmanship for a period of one (1) year from the date of purchase. To reduce the risk of property damage due to water leakage, this filter **MUST** be installed in accordance with the manufacturer's specifications and installations. This filter unit must be replaced every 6 months, at the rated capacity, or sooner if reduced water flow occurs. Protect from freezing. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.